



# CLOCKGUARD

**The Safe, Beautiful way to protect you wall mounted controller.**

- Never any sharp corners or edges
- Unique design safe for children & pedestrians
- Complete access for programming & service work
- Powder coated for durability and low maintenance
- Installation takes just minutes with hardware provided
- Custom sizes can be made to your specifications
- Open strip under the unit allows access for power and controller wiring
- Rugged construction prevents vandalism and theft.
- Internally mounted hinges for added security

**\* Ideal for Apartment houses, Schools, Public housing, Parks, Shopping Centers or anywhere the general public has access to you controller \***

The **ClockGuard™** Wall Mounted Enclosure is the safe, attractive way to protect wall mounted sprinkler controllers. The clean, no-nonsense lines and rounded corners not only provides vandalism and theft protection, but also safeguard passing pedestrians (especially since these items are occasionally installed at head height).

With the two sizes of enclosures offered below, GuardShack has a standard unit available for virtually all wall mounted timers. Hinges can be installed either on the inside of the unit or on the outside, and tamper resistant mounting hardware is provided. Units come hinged on the right side, standard.

The **ClockGuard™** padlock feature is especially important to turf and landscape managers who wish to keep unauthorized people from adjusting their timers.

Special Order **ClockGuard™** enclosures are available as well. Use special order **ClockGuards™** to cover mounted lights, emergency lights and various signs. Larger wall mounts to cover backflow assemblies, gas meters and various valves and fixtures located next to walls. Consult the factory for special order details, pricing and delivery.

ClockGuard™ Enclosures for Wall Mounted Sprinkler Controllers			
Model	ClockGuard Internal	Sprinkler	Miscellaneous Other Uses
CG-1	11"L x 11"H x 6½"D	Small	Transformers, Outdoor Light,
CG-2	17"L x 14"H x 7½"D	Larger or Deeper	Multiple Items as listed

\* General guideline only. Always measure the exact outside dimensions of your controller when sizing your ClockGuard™ enclosure

## ClockGuard™ Specification

¾" .065 wall tubing  
 ½" x ½" x ⅙" steel angle iron  
 ½" #13 gauge diamond pattern flat rolled expanded steel with all welded construction 2" on center  
 Expanded metal die formed for uniformity

State-of -the-art five part metal cleaning process and iron phosphate solution treatment. Units preheated before applying 1.5-2.0 mil thickness polyester powder to A.S.T.M. D-2794 Impact Resistant Specifications and A.S.T.M. D-3359 Adhesive Specifications. Standard Color GR-21 "Grey"

Warranty: BPDI-GuardShack warranties this product for one (1) year from the date of purchase to be free of defects in material and workmanship. All claims must be made known to BPDI-GuardShack in writing within 30 days of the defect becoming known to the purchaser. There are no warranties that extend beyond those described herein, either expressed or implied. BPDI-GuardShack reserves the sole right, at it's own option to repair or replace any defective product, and shall exclude any damage caused by accident, misuse or abuse of the product. In no case shall BPDI-GuardShack be liable for any incidental or consequential damages what-so-ever.

# GUARDSHACK™

Phone (602) 426-1002 \* Fax (602) 426-1005 \* 1 (800) 266-5411

GuardShackEnclosures.com