

12-0-0 Chelated **Iron Plus**

Formulated for Turf, Ornamental, and Foliar

GUARANTEED ANALYSIS

Total Nitrogen (N)......12.00% 12.00%. Úrea Nitrogen

Derived From: Urea

Manganese(Mn)......2.00% 2.00% Chelated Manganese Iron (Fe)......6.00% 6.00% Chelated Iron Sulfur (S)......4.00% 4.00% Combined Sulfur

Derived From:

Manganese Sulfate, Iron Sulfate, Citric Acid, **EDTA**

F1560

COMPATIBILITY

Do not mix with other fertilizers containing phosphate or Calcium. This product can be used with most crop protection chemicals. Use a "jar compatibility" test with unfamiliar mixes. 250 gal-Item #510979-250

2.5 gal -Item #510979

30 gal -Item #510979-30

Weight per gallon: 11.2 lbs

Lesco 12-0-0 Chelated Iron Plus is compatible with many pesticides and fertilizers. Avoid spraying in periods of low humidity or when turf/plant is under stress. Early morning, late afternoon, or cloudy days are preferable to hot, dry conditions. Avoid watering for 24 hours after application for optimal results.

Application	Rate
Greens and Tees	Apply 2 to 5 ounces of LESCO 12-0-0 Chelated Iron Plus in sufficient water for thorough coverage (usually 3 -5 gallons per 1,000 sq. ft.)
Fairways, Lawns, Athletic Fields and Other	Apply 2 to 3 gallons per acre of LESCO 12-0-0 Chelated Iron Plus in sufficent water for thorough coverage or approximately 130 - 218 gallons per acre. Apply 6 to 9 ounces in 3-5 gallons of water per 1,000 sq. ft. to smaller areas.
Ornamental:	Foliar - Mix 1 gallon of LESCO 12-0-0 Chelated Iron Plus in 100 gallons of water and spray foliage to the point of runoff. For best results apply to actively growing foliage. For optimal results avoid watering for 24 hours.
Soil Application	Mix 3 to 5 gallons of LESCO 12-0-0 Chelated Iron Plus in 100 gallons of water and inject within the drip line approximately 1 to 2 gallons of finished solution.

CONDITIONS OF SALE

Lesco, Inc. offers this product for sale subject to the following conditions of sale, which can be varied only by written agreement from Lesco, Inc.

Lesco, Inc. warrants that the chemical composition of the product conforms to the label description and to be reasonably fit for the purpose referred to in the "Directions for Use" on the label.

Risk: Because the time, place, rate of application, and other conditions of use are beyond the sellers control, the buyer assumes all risks associated with the storage, handling, use, or application of this product. Limit of Liability: Lesco, Inc. 's liability from the storage,

handling, and use of this product is limited to the replacement of the product or refund of the purchase price.

Precautionary Statements: Use/store in cool, well ventilated areas. Avoid Contact with eyes. Avoid prolonged or repeated breathing of vapors. Avoid prolonged or repeated contact with skin. Keep away from any sources of heat or flames. Store totes or small containers out of direct sunlight. Do not allow release to aquatic waterways. Wear protective apron, gloves, and eye/face protection.

Manufactured by: ProPlus Products, Inc. 149 County Line Road East Bowling Green,FL 33834 1-866-375-2487

FL Reg #F1560

Manufactured For: Lesco. Inc. 1385 East 36th Street Cleveland, OH 44144

510979-30

We recommend following the Green Industries BMP's

Lesco is a registered trademark, the sweeping design is a trademark of Lesco Technologies, Inc.