



Enhanced Calcitic Limestone

50 lb COVERS 8,500 sq ft

SGN 210

GUARANTEED ANALYSIS

DIRECTIONS FOR USE: This LESCO product is a professional quality turf amendment for use on all lawn areas. The best results with this product are obtained when it is applied to actively growing grass, and watered into the turf soon after application. May be applied to bare soil prior to seed or sod application. Avoid mowing immediately following application to prevent pick-up.

For best results, sweep or blow the fertilizer off walks and painted surfaces following application to avoid discoloration.

Do not apply near water, storm drains or drainage ditches. Do not apply if heavy rain is expected. Apply this product only to your lawn\garden, and sweep any product that lands on the driveway, sidewalk, or street back onto your lawn\garden.

For additional LESCO, Inc. product assistance call 1-800- 347-4272.

Application Rates:

Maintenance Rate = covers approx. 8,500 sq ft at an app rate of 6 lbs of product per 1,000 sq ft and
High rate = covers approx. 4,200 sq ft at an app rate of 12 lbs of product per 1,000 sq ft

Spreader Setting Chart

Spreader	Maintain Soil pH		Raise Soil pH	
	6.0 lbs/1000 sq. ft	12.0 lbs/1,000 sq ft	6.0 lbs/1000 sq. ft	12.0 lbs/1,000 sq ft
	Bag covers 8,500 sq. ft.		Bag covers 4,200 sq. ft.	
LESCO	20	26	20	26
PermaGreen	20	26	20	26
Cyclone etc	6	8	6	8
Vicon	34	52	34	52
Lely	7	10	7	10

Total Calcium (Ca) 36.00%
 Total Magnesium (Mg) 0.5%
 Calcium Carbonate (CaCO3) 95.00%
 Magnesium Carbonate (MgCO3) 0.9%
 Calcium Carbonate Equivalent (CCE) 91.00%
 Effective Neutralizing Value (ENV) 88.27%
 Maximum Moisture Content 1.0%
 Derived from calcitic limestone.

Fineness before Prilling

4 Mesh Sieve 100% Passing
 8 Mesh Sieve 100% Passing
 10 Mesh Sieve 100% Passing
 20 Mesh Sieve 100% Passing
 50 Mesh Sieve 100% Passing
 60 Mesh Sieve 95% Passing
 100 Mesh Sieve 95% Passing
 200 Mesh Sieve 90% Passing

Non-Plant Food Ingredients: 0.50%

ALSO CONTAINS NON PLANT FOOD INGREDIENTS

2.00% Humic Acids from Leonardite. Humic Acids acts as a complexing agent.
 8.00% Lignin Sulfonate act as a water soluble binding agent
 90.00% Total Other Ingredients

FL: This product requires 1978 lbs. to be equal to 1 ton of standard liming material.

KS: ECC = 88.73%
 OH: ENP = 1765.76 lbs. per ton
 MN: 1765.76 lbs. ENP per ton
 OK: ECCE = 88.73%
 MS: RNV = 91%
 OR Lime Score: 90
 NC: 2198 pounds of this material equals 1 ton of standard liming material.
 NH Classification of Fineness: Coarse Size
 TN: RNV = 92.18%
 WI Neutralizing Index: 89.18%
 WI Index Zone: 80-89
 Meets WV fineness classification for pulverized.



WARNING

Harmful if inhaled. Eye and skin irritant. Avoid breathing dust. Avoid contact with skin, eyes, or clothing. Wash thoroughly with soap and water after handling.

CONDITION OF SALE AND LIMITATION OF WARRANTY AND LIABILITY

NOTICE: Read the entire Directions for Use and Conditions of Sale and Limitation of Warranty and Liability before buying or using this product. If the terms are not acceptable, return the product at once, unopened, and the purchase price will be refunded.

The Directions for Use of this product must be followed carefully and completely. It is impossible to eliminate all risks inherently associated with the use of this product. Buyer and/or User assume all risks of ineffectiveness or other unintended consequences or damages that may result from conditions outside or beyond the control of LESCO, Inc. including but not limited to such factors as manner of use or application, weather or weather conditions outside the range considered normal at the application site or for the time period in which the product is applied, the presence of other materials, incompatible products, or other influencing factors which are beyond the control of LESCO, Inc.. All such risks shall be assumed by Buyer and/or User, and Buyer and/or User agrees to hold LESCO, Inc. harmless for any claims relating to such factors.

LESCO, Inc. warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated in the Directions for Use, subject to the inherent risks referred to above, when used in accordance with the Directions for Use under normal use conditions. This warranty does not extend to the use of this product contrary to label instructions, or under abnormal conditions or under conditions not reasonably foreseeable to or beyond the control of LESCO, Inc. and Buyer and/or User assume the risk of any such use.

LESCO, INC. MAKES NO WARRANTIES OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE NOR ANY OTHER EXPRESS OR IMPLIED WARRANTY EXCEPT AS STATED ABOVE.

THE EXCLUSIVE REMEDY OF THE BUYER AND/OR USER AND THE EXCLUSIVE LIABILITY OF LESCO, INC. FOR ANY AND ALL CLAIMS, LOSSES, INJURIES OR DAMAGES (INCLUDING CLAIMS BASED ON BREACH OF WARRANTY, CONTRACT, NEGLIGENCE, TORT, STRICT LIABILITY OR OTHERWISE) RESULTING FROM THE USE OR HANDLING OF THIS PRODUCT, SHALL BE THE RETURN OF THE PURCHASE PRICE OF THE PRODUCT OR, AT THE ELECTION OF LESCO, INC. REPLACEMENT OF THE PRODUCT, OR IF NOT ACQUIRED BY PURCHASE, REPLACEMENT OF SUCH QUANTITY. IN NO EVENT SHALL LESCO, Inc., BE LIABLE FOR ANY INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES. LESCO, Inc. offers this product, and Buyer and/or User accepts it, subject to the foregoing Conditions of Sale and Limitation of Warranty and Liability, which may not be modified except by written agreement signed by a duly authorized representative of LESCO, Inc.

Information concerning the raw materials composing this product can be obtained by writing to: LESCO, Inc., Attn: RA Dept, 1385 East 36th Street, Cleveland, Ohio 44114-4114, referring to the item number found on this bag.

Information regarding the contents and levels of metals in this product is available on the Internet at <http://www.aapfco.org/metals.html>

LESCO and Spar-TECH are registered trademarks and the sweeping design is a trademark of LESCO, Inc. Cyclone and Spyker are registered trademarks of Spyker Spreaders, LLC. Lely is a registered trademark of C Van Der Lely N.V. Rev. 5/14/24 VT

F1560

NET WEIGHT 50 lb (22.7 kg)

Manufactured for: LESCO, Inc.
1385 East 36th Street
Cleveland, OH 44114-4114

511615

