

IESCO

CHANGING

FLOIQ™ VARIABLE FLOW TECHNOLOGY

Patented technology provides customized performance per application.

VARIABLE FLOW from 0.1 - 0.6 GPM ~ 90PSI MAX

- · Adjust flow rate for a broad range of applications & uses.
- Eliminates over-application of product.
- Consistent application rate increases efficiency on the job!

18V 2.0AH LI-ION BATTERY POWERED

Provides consistent pressure, saves time and energy!

SEALED and WATER RESISTANT BATTERY COMPARTMENT and SHROUD

for internal protection from the elements.

DELUXE HARNESS with PADDED WAIST BELT provides all day comfort.

50" HEAVY-DUTY KINK-RESISTANT HOSE No Kinking/No Damage.

PROFESSIONAL SHUT-OFF with COMFORT GRIP, LOCK & FILTER

can be easily operated with all required PPE.

POLY-LINED STAINLESS STEEL WAND

is stronger and more durable than brass.

VITON® SEALS resist harsh chemicals.



LITHIUM-ION **BATTERY** and 110V FAST **CHARGER** (Included)

18 / **ERGONOMICALLY** DESIGNED FOR THE HARSHEST WORK **ENVIRONMENTS.**

TESCO

User-controlled VARIABLE FLOW from 0.1 to 0.6 GPM

INTELLIGENT PRESSURE SWITCH

Internal pressure switch automatical**l**y toggles between high and low to manage peak pressure at the low (1-3) and high (4-10) settings.

INTELLIGENT FLOW MONITORING

Automatically adjusts to maintain consistent output pressure and flow for any dial setting regardless of battery life.

18V LITHIUM-ION
VARIABLE FLOW
BACKPACK SPRAYER

POWER



LITHIUM-ION POWERED

VARIABLE FLOW BACKPACK SPRAYER

HEAVY-DUTY KINK-RESISTANT

PROFESSIONAL SHUT-OFF with COMFORT GRIP, **LOCK & FILTER**

WIDE 4.75" FILLING CAP

NOZZLE STORAGE CLIP

CONVENIENT VERTICAL WAND STORAGE

21" POLY-LINED STAINLESS STEEL WAND STRONGER AND MORE **DURABLE THAN BRASS**

DELUXE HARNESS WITH REMOVABLE WAIST BELT



TURF & AGRICULTURE



PEST CONTROL



CONSTRUCTION

CUSTODIAL

Specifications		
Empty Weight	16 Lbs	
Tank Capacity	4 Gallons	
Wand	21" Poly-Lined SS	
Hose Length	50" Kink-Resistant	
Quick Change Tips	7 Included	
Pallet Quantity	20	

Compatible with Popular Formulations

Flow Rate	0.1 TO 0.6 GPM	
Pressure Range	2 TO 90 PSI	
Spray Distance	UP TO 34 FEET	
Spray Height	UP TO 35 FEET	
Spray Duration Per Charge	UP TO 4 HOURS	
Spray Volume Per Charge	50 GALLONS	

Optional Accessories

18V Li-ion Battery Pack, 2.0 Ah	No. 183612
18V Li-ion Battery Pack, 4.0 Ah	No. 183613
18V Li-ion Fast Charger, 110V input	No. 183614
18V Li-ion Compact Charger, 12V input	No. 183615
18V Li-ion Vehicle Charger, 12V input	No. 183831



CAP WAND GROOVE FOR TIGHTENING & LOOSENING



LED BATTERY LIFE INDICATOR



NOZZLE STORAGE CLIP



7 SPRAYING NOZZLES



ADJUSTABLE BRASS

JET STREAM Adjusts from solid Pinpoint stream stream to fine mist. for targeted applications from a distance.



FOAMING Creates a lite

foam to improve weed killing performance and track where you spray.











NARROW FAN (Yellow)

Flat spray for precision

spraying.



HIGH VOLUME FOAMING



















Flat spray for very Flat spray broad coverage and for broader higher viscosity coverage.



Broad foam coverage for horizontal and vertical surfaces.

