



Stronger Together

Lithium-Ion Powered **NONORE PUNPING!** *Superior control with greater productivity*

7.2v LITHIUM-ION POWERED SPRAYER Maintains optimum pressure range (16-23psi).

18" BRASS WAND with **PROVEN BRASS VALVE** Brass durability and pro-level performance.

INCLUDES INTERCHANGEABLE 4-WAY and 50015ESS FAN NOZZLE

Meets labeling requirement for all formulations.

HEAVY-DUTY 50" REINFORCED RUBBER & NYLON HOSE

Provides durable dependable service.

64" PRO SHOULDER STRAP with PAD

For all day comfort.

VITON[®] SEALS Field tested for maximum compatibility.

PUMP WALL CHARGER included.

INCLUDES TANK CAP For safe storage and transport.



1 Ga LITHIUM-ION SPRAYER









CHEMICALLY SPRAYS RESISTANT TO UP TO **3hrs.** MODERN AGGRESSIVE CONTINUOUSLY FORMULATIONS PER CHARGE



TERMINATE







SPRAYER

Heavy-Duty 50" Reinforced Rubber & Nylon Hose. Maintains flexibility for years of use.

Integrated Carry Handle and Rubber Booted Power Switch and Battery Status Light and Charger Port.



7.2v Lithium-ion Powered Compressor provides Time Saving, Consistent Uninterrupted Pressure through-out your applications.

> Re-pressurizing 2 minutes/gallon while spraying with a 3-hour run time.



18" Brass Wand and Professional Shut-Off with Comfort Grip and Internal Filter. Operational Superiority and ease of maintenance.

Pressure Release Valve prevents "spray back" relieve pressure prior to opening.

64" Pro Shoulder Strap with Comfort Pad for easy of operation and comfortable use.

Minimize one-hand carry freeing the use of both hands.

4-Way Brass Nozzle for precise applications with coarse & fine fan, C&C straw and pin stream. Also includes **50015ESS** tip for full range spray coverage.

Integrated Wand Storage Keeps wand safely stored during transportation.

LESCO

yer

Pump Spr

Tear-Drop Shaped Tank

for lower center of gravity to prevent accidental spills.

High-Performance Application Equipment for Modern Technicians. Designed by PCO Professionals for PCO Professionals on the foundation of Application Economics.

Specifications

Empty Weight	6 LBS
Tank Capacity	1 Gallons
Wand	18" Brass
Nozzles	4-Way and 50015ESS
Hose Length	50" Nylon Reinforced
In-Valve Filter	Replaceable 250 Mesh
Pallet Quantity	50 units
Flow Rate	0.085 GPM at 20 PSI
Spray Duration Per Charge	UP TO 3 HOURS
Spray Volume Per Charge	20 GALLONS
UPC	8 41688 00737 6

Key Service Parts & Accessories

Pump Zero Kit	184163
18" Wand	182874
4-Way Nozzle	182912
Shut-off Assembly	182867
Hose Assembly	182893
Pro Shoulder Strap	184536

Spray Pattern Accuracy is fundamental to **Safety, Efficiency** and **Compliance**. Our **Technology** makes you a better applicator by eliminating the fluctuation in spray patterns that manual pumps simply cannot.



SiteOne LANDSCAPE SUPPLY Stronger Together

ALSO ACCEPTS TEEJET STYLE NOZZLES

©Copyright 2022 The Fountainhead Group, Inc. All rights reserved.