

POWER MELT®

PERFORMANCE ICE MELTER

SUB ZERO MELTING 

POWERED BY:
PROPEL®
DE-ICER ACCELERATOR

CAPS™ COMPACTED ACCELERATION PARTICLES

50 LBS
22.7 KG

POWER MELT® PERFORMANCE ICE MELTER

POWER MELT®

PERFORMANCE ICE MELTER

DIRECTIONS

Spread evenly over icy surface, using a cup, scoop or spreader at a rate of 1/4 to 1/2 cup per square yard. **DO NOT PILE.** When melting has occurred and ice separates from surface, remove slush and water to prevent re-freezing. In snow deeper than two inches, all de-icers are impractical. Shovel first, then spread **POWER MELT®** to melt any ice or hard packed snow left behind.

APPLICATION GUIDELINES

POWER MELT® is recommended for de-icing asphalt and concrete surfaces that have been designed and constructed for winter weather conditions and de-icer usage. **POWER MELT®** will not chemically attack asphalt or concrete. Melt water from the de-icing process may soak into porous concrete and re-freeze, creating pressure within the concrete structure. Concrete that lacks the strength to withstand this pressure may spall or scale. Concrete is resistant to scaling damage if it is air entrained, mixed, placed and cured according to the recommendations of the American Concrete Institute Committee 301.

WARNING

MAY CAUSE EYE IRRITATION | MAY CAUSE SKIN IRRITATION | MAY BE HARMFUL IF SWALLOWED

PRECAUTIONS: Avoid contact with eyes, skin or clothing. Do not take internally. Wash thoroughly after handling. Wear eye and face protection. Do not eat, drink or smoke when using this product.

FIRST AID: In case of contact with eyes, immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. If effects occur, consult a physician preferably an ophthalmologist. If swallowed, do not induce vomiting. Give one cup (8 ounces or 240 ml) of water or milk if available and transport to a medical facility. Never give anything by mouth unless person is fully conscious.

OSSIAN INC. / 635 S. ELMWOOD AVE / DAVENPORT, IOWA 52802

POWER MELT® is not recommended for de-icing concrete that is less than one year old, precast steps, masonry (stone, brick, mortar joints), existing concrete that has exposed aggregate, is precast, pre-stressed, chipped, cracked, spalled or weathered. **POWER MELT®** is not recommended for de-icing surfaces composed of wood or metal.

Use entrance mats to avoid tracking snow, slush, or residual de-icer onto interior floors that may become slippery when wet. Avoid exceeding recommended application rates as interference with traction or footing may result.

DISPOSAL

Dispose of empty container in compliance with federal, state/provincial and local laws and regulations.

ACTIVE INGREDIENTS:	CAS NUMBER
Sodium Chloride	07647-14-5
Propel®	Proprietary
C.A.P.S.™	Proprietary

PROPEL® U.S. PATENT

POWER MELT®, PROPEL®, C.A.P.S.™ are registered trademarks of OSSIAN INC.

Si usted no puede leer esta etiqueta contacte a alguien que puede para asegurar apropiado uso.

