

1.	PRODUCT & COMPANY IDENTIFICATION	TRADE NAME: TechniSoil Global, Inc. PRODUCT NAME: G3® Pathway Stabilizer DISTRIBUTED BY: TechniSoil Global, Inc. 5660 Westside Rd. Redding, CA 96001		24-HOUR EMERGENCY TELEPHONE NUMBER: Chemtrec: US: 800-424-9300 INTL: 703-527-3887	
		Toll Free: 877.356.2250			
2.	COMPOSITION / INFORMATION ON INGREDIENTS	COMPONENT:	RANGE:	CAS NO:	
		Proprietary Polymer Blend	5.8% - 30.8%	Not Hazardous	
		Water	69.2% – 94.2%	Not Hazardous	
		Volatile organic compound (VOC) levels for this product are < = 5g/l.			
3.	HAZARDS IDENTIFICATION	EMERGENCY OVERVIEW PHYSICAL APPEARANCE:	HAZARD SUMMARY: CAUTION!		
		Form: Liquid Color: White, Milky Odor: Acrylic	Inhalation of vapor or mist can cause headache, nausea and irritation of the nose, throat, and lungs. May cause eye and skin irritation		
		Potential Health Effects Primary Routes of Entry: Inhalation, Eye contact, Skin contact Eyes: Direct contact with material can cause the following: slight irritation Skin: Prolonged or repeated skin contact can cause the following: slight irritation Inhalation: Inhalation of vapor or mist can cause the following: irritation of nose, throat, and lungs headache nausea			
4.	FIRST AID MEASURES	 If skin irritation persists, cal Eye contact: Rinse with pler consult a specialist. Ingestion: Drink 1 or 2 glas 	water and soap as a precaution.		
5.	FIRE FIGHTING MEASURES	 Suitable extinguishing medi Specific hazards during fire Material can splatter above Special protective equipment 	it Applicable ot Applicable May yield acrylic monomers. edia: Media appropriate for surrounding fire. ire fighting: ve 100C/212F. Dried product can burn.		



6. ACCIDENTAL PERSONAL PRECAUTIONS **RELEASE MEASURES** Use personal protective equipment. Keep people away from and upwind of spill/leak. Material can create slippery conditions. **ENVIRONMENTAL PRECAUTIONS** Keep spills and cleaning runoff out of municipal sewers and open bodies of water. METHODS FOR CLEANING UP Contain spills immediately with inert materials (e.g., sand, earth). Transfer liquids and solid diking material to separate suitable containers for recovery or disposal. 7. HANDLING & STORAGE HANDLING Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Keep container tightly closed. Do not breathe vapors, mist or gas. Further information on storage conditions: Keep from freezing - product stability may be affected. Stir well before use. **STORAGE** Storage temperature: 40 - 90 °F (4.44 - 32.2 °C) Other data: Monomer vapors can be evolved when material is heated during processing operations. See SECTION 8, for types of ventilation required. NOTE: Formaldehyde will be generated under acidic conditions. Maintain adequate ventilation under these conditions to prevent exposure to formaldehyde above the Rohm and Haas Co. recommended ceiling of 0.3 ppm. 8. EXPOSURE CONTROLS / EXPOSURE LIMIT(S) PERSONAL PROTECTION Exposure limits are listed below, if they exist. COMPONENTS VALUE REGULATION LISTING TYPE ----- Not Applicable -----EYE PROTECTION: Safety glasses with side-shields Eye protection worn must be compatible with respiratory protection system employed. HAND PROTECTION: The glove(s) listed below may provide protection against permeation. (Gloves of other chemically resistant materials may not provide adequate protection): Neoprene gloves published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.



8. EXPOSURE CONTROLS / PERSONAL PROTECTION (CONTINUED)	 RESPIRATORY PROTECTION: A respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements or equivalent must be followed whenever workplace conditions warrant a respirator's use. None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. For airborne concentrations up to 10 times the exposure limit, wear a properly fitted NIOSH approved (or equivalent) half-mask, air-purifying respirator. Air-purifying respirators should be equipped with NIOSH approved (or equivalent) N95 filters. If oil mist is present, use R95 or P95 filters. PROTECTIVE MEASURES: Facilities storing or utilizing this material should be equipped with an eyewash facility. ENGINEERING MEASURES: Use local exhaust ventilation with a minimum capture velocity of 100 ft/min. (0.5 m/sec.) at the point of vapor evolution. Refer to the current edition of Industrial Ventilation: A Manual of Recommended Practice published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems. 		
9. PHYSICAL AND	APPEARANCE	COMPONENT	VALUE
CHEMICAL PROPERTIES	Form: liquid Colour: white milky	рН	7.0 - 9.0
	Odor: acrylic	Boiling point/boiling range	100 °C (212.00 °F) Water
	,	Melting point/range	0 °C (32 °F)
		Flash point	Noncombustible
		Lower explosion limit	Not Applicable
		Upper explosion limit	Not Applicable
		Vapour pressure	17.0 mmHg at 20 °C (68.00 °F) Water
		Relative vapour density	<1.0 Water
		Water solubility	Miscible
		Relative density	1.00 - 1.20
		Viscosity, dynamic	250.000 mPa.s maximum
		Evaporation rate	<1.00 Water
		Percent volatility	49 - 51 % Water
		Volatile organic compounds (VOC)	<= 5 g/L
		NOTE: The physical data prese should not be construed as a s _l	ented above are typical values and pecification.
10. STABILITY & REACTIVITY	Hazardous reactions	None kr	nown. Stable
			re no known materials which are
		•	atible with this product.
	Polymerization	Product	will not undergo polymerization.



11. TOXICOLOGICAL INFORMATION

No data are available for this material. The information shown is based on profiles of compositionally similar materials.

Acute oral toxicity	LD50 rat > 5,000 mg/kg	
Acute dermal toxicity	LD50 rabbit > 5,000 mg/kg	
Skin irritation	rabbit May cause transient irritation.	
Eye irritation	rabbit No eye irritation	

12. ECOLOGICAL INFORMATION

THERE IS NO DATA AVAILABLE FOR THIS PRODUCT.

13. DISPOSAL ENVIRONMENTAL PRECAUTIONS CONSIDERATIONS Keep spills and cleaning runoff out

Keep spills and cleaning runoff out of municipal sewers and open bodies of water. **DISPOSAL WASTE CLASSIFICATION:** When a decision is made to discard this material as supplied, it does not meet RCRA's characteristic definition of ignitability, corrosivity, or reactivity, and is not listed in 40 CFR 261.33. The toxicity characteristic (TC), however, has not been evaluated by the Toxicity Characteristic Leaching Procedure (TCLP). Coagulate the emulsion by the stepwise addition of ferric chloride and lime. Remove the clear supernatant and flush to a chemical sewer. For disposal, incinerate or landfill at a permitted facility in accordance with local, state, and federal regulations.

14. TRANSPORT INFORMATION

DOT	Not regulated for transport
IMO/IMDG	Not regulated (Not hazardous)

15. REGULATORY INFORMATION

WORKPLACE CLASSIFICATION	This product is considered non-hazardous under the OSHA Hazard Communication Standard (29CFR1910.1200). This product is not a 'controlled product' under the Canadian Workplace Hazardous Materials Information System (WHMIS).
SARA TITLE III: SECTION 311/312 CATEGORIZATIONS (40CFR370):	This product is not a hazardous chemical under 29CFR 1910.1200, and therefore is not covered by Title III of SARA.
SARA TITLE III: SECTION 313 INFORMATION (40CFR372)	This product does not contain a chemical which is listed in Section 313 at or above de minimis concentrations.
CERCLA INFORMATION (40CFR302.4)	Releases of this material to air, land, or water are not reportable to the National Response Center under the Comprehensive Environmental Response, Compensa- tion, and Liability Act (CERCLA) or to state and local emergency planning committees under the Superfund Amendments and Reauthorization Act (SARA) Title III Section 304.



TechniSoil G3[®] Pathway Stabilizer

15. REGULATORY INFORMATION (CONTINUED)	US. TOXIC SUBSTANCES CONTROL ACT (TSCA):	All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.
	PENNSYLVANIA	Any material listed as "Not Hazardous" in the CAS REG NO. column of SECTION 2, Composition/Information On Ingredients, of this MSDS is a trade secret under the provisions of the Pennsylvania Worker and Community Right-to-Know Act.

16. OTHER INFORMATION

HAZARD RATING:

	HEALTH	FIRE	REACTIVITY
HMIS	1	0	0

LEGEND

.....

ACGIH	American Conference of Governmental Industrial Hygienists
ВАС	Butyl acetate
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short Term Exposure Limit (STEL)
TLV	Threshold Limit Value
TWA	Time Weighted Average (TWA)
" "	Bar denotes a revision from prior SDS
	•

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication.

The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.