# **Andersons Golf Products**

# Turf Fertilizer **28-0-10**

- Contains slow release nitrogen for extended feeding
- Contains Sulfate of Potash
- Provides Iron and Manganese to prevent turf deficiencies

# **Guaranteed Analysis**

Total Nitrogen (N)	28.00%
Soluble Potash (K <sub>2</sub> O)	10.00%
Sulfur (S)	4.96%
1.56% Free Sulfur (S)	
3.40% Combined Sulfur (S)	
Iron (Fe)	3.00%
Manganese (Mn)	1.00%
0.14% Water Soluble Manganese (Mn)	

Derived from urea, potassium sulfate, polymer coated sulfur coated urea, ferric oxide, manganous oxide, manganese sulfate.

\*16.80% slowly available urea nitrogen from polymer coated sulfur coated urea.

# F002091

Information regarding the contents and levels of metals in this product is available on the internet at http://www.aapfco.org/metals.html

## **DIRECTIONS FOR USE**

Apply only as directed. Use Andersons Golf Products Turf Fertilizer 28-0-10 on actively growing fairways and roughs whenever a high nitrogen feeding with quick initial green-up and controlled-release nitrogen is desired.

# **Application Rates:**

MEDIUM: 3.57 lbs/1,000 sq. ft.

# **FLORIDA APPLICATIONS:**

We recommend that you follow the Florida Green Industries BMP's at: http://www.flrules.org/Gateway/reference.asp?No=Ref-04706 We recommend that you follow the Florida Golf Course BMP's at: http://www.flrules.org/Gateway/reference.asp?No=Ref-04702

# For all applications:

- For use on fairways and roughs.
- Apply to dry foliage.
- Water in after application with a minimum of 0.2 inches to help move particles into the turf canopy.
- Do not collect clippings for at least one mowing following application to avoid particle pick-up.
- Apply at MEDIUM RATE.

**Note:** This product contains the micronutrient iron for extra greening and to help prevent iron deficiency. Iron may stain concrete and other surfaces. Misapplied product to these surfaces should be removed promptly by sweeping or blowing. DO NOT WASH OFF WITH WATER.

Do not apply near water, storm drains or drainage ditches. Do not apply if heavy rain is expected. Apply this product only to your lawn and sweep any product that lands on the driveway, sidewalk or street, back onto your lawn.

# STORAGE AND USE

Store in a clean, dry place. Reseal opened bag by folding top down and securing. Use only in clean, dry spreaders. Do not leave unused product in spreaders.

# **IMPORTANT: READ BEFORE USE:**

Read the entire Directions for Use and the Warranty Disclaimer and Limitation of Liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or Buyer accepts the following Warranty Disclaimer and Limitation of Liability:

# WARRANTY DISCLAIMER and LIMITATION of LIABILITY:

Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. Manufacturer makes NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. To the extent consistent with applicable law, it is Manufacturer's intent to LIMIT ANY LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL ECONOMIC DAMAGES to refund of purchase price or replacement of product, at Buyer's choice. To the extent consistent with applicable law, Manufacturer DISCLAIMS ANY LIABILITY FOR COMPENSATORY OR OTHER DAMAGES ARISING OUT OF ANY USE CONTRARY TO LABEL DIRECTIONS.

# **LEGAL RIGHTS:**

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE/JURISDICTION TO STATE/JURISDICTION.

Product of U.S.A.

Manufactured by: **The Andersons, Inc.**P.O. Box 119
Maumee, OH 43537
www.andersonsplantnutrient.com

# SUGGESTED SPREADER SETTINGS

Suggested spreader settings are not intended to replace calibration.

Please calibrate your spreader prior to applying product.

50 lbs feeds 14,000 sq. ft. (0.32 acre) with 1.00 lbs. N/1,000 sq. ft. at the MEDIUM RATE

SPREADER	GROUND SPEED	WIDTH OF COVERAGE	MEDIUM RATE
Andersons Model 2000 / AccuPro 2000 (cone 4); Andersons 2000 SR / SR 2000 (cone 4)	3 mph	11 feet	L 1/4
Scotts R-8A (cone 4)	3 mph	11 feet	K 1/4
Lesco 020093 (pattern 0.25)	3 mph	8 feet	E 1/2
Lesco 705698 (pattern 0.25)	3 mph	8 feet	13
Lely Models WTR, WFR, HR, 1250 (PTO at 450 rpm) Pattern I	4.5 mph	40 feet	5 1/2
Vicon (03 Series)	4.5 mph	28 feet	27



SGN 215 Net Wt. 50 Lbs. (22.68 kg) **10005147** (AGC2816M5.40)