The Andersons Turf Products

Fertilizer **24-0-11**

• Utilizes NS-54™ proprietary coated slow release nitrogen to provide uniform growth with extended nitrogen feeding

Guaranteed Analysis

Total Nitrogen (N)	24.00%
24.00% Urea Nitrogen* Soluble Potash (K ₂ O)	11.00%
Sulfur (S)	1.11%
1.11% Free Sulfur (S)	0.000/
Iron (Fe)	
Manganese (Mn)	1.00%
1.00% Water Soluble Manganese (Mn)	

F002091

FLORIDA APPLICATIONS:

We recommend that you follow the Florida Green Industries BMP's at http://www.flaes.org/pdf/BMP Book final.pdf

We recommend that you follow the Florida Golf Course BMP's at http://www.flaes.org/pdf/glfbmp07.pdf

DIRECTIONS FOR USE

Apply only as directed. Apply during the growing season.

Application Rates:

LIGHT: 2.08 lbs/1,000 sq. ft. LOW: 3.12 lbs/1,000 sq. ft. MEDIUM: 4.16 lbs/1,000 sq. ft. HIGH: 5.20 lbs/1,000 sq. ft.

NOTE: For those states with nitrogen application restrictions, including Maryland, New Hampshire, New Jersey and Virginia, do not apply more than 3.12 lbs. of this product per 1,000 sq. ft.

For all applications:

- Apply to dry foliage.
- Water in after application with a minimum of 0.2 inches to help move particles into the turf canopy.
- Do not collect clippings for at least one mowing following application to avoid particle pick-up.

Cool Season Grasses:

- Apply at the LIGHT to MEDIUM RATE.
- Apply at the LIGHT to LOW RATE when temperatures exceed 85°F.

Warm Season Grasses:

 Apply at the MEDIUM or HIGH RATE every 4-6 weeks during the period of active growth.

STORAGE AND USE

Store in a clean, dry place.
Reseal opened bag by folding top down and securing.
Use only in clean, dry spreaders.
Do not leave unused product in spreaders.

Do not apply near water, storm drains or drainage ditches. Do not apply if heavy rain is expected. Apply this product only to your lawn and sweep any product that lands on the driveway, sidewalk or street, back onto your lawn.

Note: This product contains the micronutrient iron for extra greening and to help prevent iron deficiency. Iron may stain concrete and other surfaces. Misapplied product to these surfaces should be removed promptly by sweeping or blowing. DO NOT WASH OFF WITH WATER.

IMPORTANT: READ BEFORE USE:

Read the entire Directions for Use and the Warranty Disclaimer and Limitation of Liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or Buyer accepts the following Warranty Disclaimer and Limitation of Liability:

WARRANTY DISCLAIMER and LIMITATION of LIABILITY:

Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. Manufacturer makes NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. To the extent consistent with applicable law, it is Manufacturer's intent to LIMIT ANY LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL ECONOMIC DAMAGES to refund of purchase price or replacement of product, at Buyer's choice. To the extent consistent with applicable law, Manufacturer DISCLAIMS ANY LIABILITY FOR COMPENSATORY OR OTHER DAMAGES ARISING OUT OF ANY USE CONTRARY TO LABEL DIRECTIONS.

LEGAL RIGHTS:

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE/JURISDICTION TO STATE/JURISDICTION.

Product of USA

Manufactured by: The Andersons, Inc. P.O. Box 119 Maumee, OH 43537 www.andersonsplantnutrient.com

NS-54 is a trademark of The Andersons, Inc.

Suggested Spreader Settings

These suggested spreader settings are not intended to replace calibration.

Please calibrate your spreader prior to applying product.

50 lbs. feeds 24,000 sq. ft. (0.55 acre) with 0.50 lbs. N/1,000 sq. ft. at the LIGHT RATE

50 lbs. feeds 16,000 sq. ft. (0.37 acre) with 0.75 lbs. N/1,000 sq. ft. at the LOW RATE

50 lbs. feeds 12,000 sq. ft. (0.28 acre) with 1.00 lbs. N/1,000 sq. ft. at the MEDIUM RATE

50 lbs. feeds 9,600 sq. ft. (0.22 acre) with 1.25 lbs. N/1,000 sq. ft. at the HIGH RATE

				SPREADER SETTINGS		
SPREADER	GROUND SPEED	WIDTH OF COVERAGE	LIGHT RATE 2.08 lbs/1,000 sq. ft.	LOW RATE 3.12 lbs/1,000 sq. ft.	MEDIUM RATE 4.16 lbs/1,000 sq. ft.	HIGH RATE 5.20 lbs/1,000 sq. ft.
Andersons Model 2000 / AccuPro 2000 (cone 4); Andersons 2000 SR / SR-2000 (cone 4)	3 mph	12 feet	К	L 1/4	M 1/2	N 3/4
Andersons LCO-1000	3 mph	12 feet	К	L 1/4	M 1/2	N 3/4
Scotts R-8, R-8A (cone 4)	3 mph	12 feet	J	K 1/4	L 1/2	M 3/4
Lesco 020093 (pattern 0.5)	3 mph	10 feet	D 1/2	E 1/2	F 1/2	G 1/2
Lesco 705698 (pattern 0.5)	3 mph	10 feet	11	13	15	17
Lely Models WTR, WFR, HR, 1250 (PTO at 450 rpm) Pattern I	4.5 mph	40 feet	4 1/2	5 1/4	6	6 3/4
Vicon (03 Series)	4.5 mph	36 feet	19	24	29	34

Net Wt. 50 Lbs. (22.68 kg)



APT2412M5.40